



Koreton

Technical Data



SIRIM
ECO-LABEL
Licence No : ECO 013



032-124-1715
Environmentally Preferred Coating

Koreton is a vinyl acrylic co-polymer project emulsion paint, which is formulated with cost efficiency for the decoration of interior wall. It's high build properties provides a smooth and matt finishing with good opacity, helps to cover-up any wall imperfections. Koreton exhibit fungus resistance and is produced with environmental-friendly ingredients, it is accredited with Singapore Green Label and SIRIM Eco-label legislation.

Recommended Use : Koreton interior emulsion paint is widely used as an economy emulsion paint in the housing and construction industries. It truly perform as a reliable and economy solution for used as a decorative interior finishing for the interior walls, ceilings, plaster masonry, hard and soft boards in the building industries.

Technical Information

Vehicle Type	: Polyvinyl Acetate
Finish	: Matt
Component	: Single pack
Color	: Refer to Koreton Color Card (Please consult your KCC representative)
Volume Solids	: White 38% (normally), varies depending on colors
Drying By	: Evaporation, Coalescence
Flash Point	: Non Flammable
Specific Gravity	: 1.38, varies depend on colors
Dry Film Thickness (Dft)	: 25 to 30 microns / coat
Viscosity (ASTM D-562)	: 100 KU (± 5)
Shelf Life	: Minimum 1 year - unopened

Application Details

Apply Over	: Prepared Substrate or New Masonry
Primer / Sealer	: E-Prime / Wall Sealer
Application Methods	: Brush / Roller / Spray
Wet Film / Coat	: Approx. 75 - 100 microns
Dry Film / Coat	: Approx. 30 - 35 microns
Drying Time	: Touch 30 mins Recoat 60 mins
Theo. Spreading Rate	: Approx 13 m ² / litre*
No of coats	: 2 coats
Clean Up	: Clean Water
Packaging	: 7 / 18 litres

* When estimating paint quantity, please make provision for spray or application losses due to spreading rate may varies depending on the surface roughness and porosity of the substrate.

Surface Preparation

New Masonry Substrates

Allow all new surfaces to dry out thoroughly, preferably for at least 28 days drying time or check moisture content for less than 12%. Surface imperfections, misalignments and protrusions shall be made good and patched up

Previously Painted Surface

All loose or defective paintwork or powdery residues shall be thoroughly removed by high pressure water jet cleaning. Treat any areas affected by mould, lichens, algae and moss with "KCC Fungicidal Solution". Make good minor defects with an appropriate suitable exterior putty sealant.

Typical Painting System

<u>Substrate</u>	<u>Sealer (1 coat)</u>	<u>Finishing (2 coats)</u>
New and bare surface	E-Prime / KCC Sealer	Koreton
Previously painted surface	E-Prime / KCC Sealer	Koreton

Application

Stir thoroughly to a uniform consistency before use. Thinning is normally not necessary, however if required except for absorbent surfaces and better workability, thin with a small quantity of clean water.

Suitable for application by brush, roller or spray. Apply paint evenly by brush or roller, and avoid any missing areas. Spraying is recommended, and typical equipment, especially airless spray should employ a fluid tip / needle size at least 0.021".

Cleaning

Remove as much product as possible from application equipment before cleaning. Clean equipment immediately after use in warm soapy water and rinse thoroughly. Do not empty product into drains or watercourses. Replace lid firmly.

Technical Services

KCC maintains a technical division to investigate and advise on all problems related to our product application. The division will advise on the correct selection of and specification for the required painting system. Contact the division through KCC Sales department.

Safety Precaution

- Ensure good ventilation during application and drying.
- Avoid contact with skin and eyes.
- In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
- After contact with skin, wash immediately with plenty of soap and water.
- When spray, do not breathe in spray mist, wear suitable respiratory protective equipment.
- Keep out of reach of children.

Disclaimer : The above information is given to the best of our knowledge based on laboratory testing and practical experiences. The information in this data sheet may be subject to changes from time to time and without notice due to production refinements arising from continuing research and evaluation programmes, which may occasionally result in marginal changes in the coating properties.