

RoofCare

Exterior Emulsion

Product Description

RoofCare is a premium full acrylic water based finish. It provides good UV durability, algae resistance and colour fastness. It is low VOC and APEO-free.

Recommended Use

Exterior use for concrete, masonry, soft board and roof tiles suitable for new and repainting projects.

Product Information

Binder	: Full Acrylic
No. of Components	: 1
Solids (% by Volume)	: 40 ± 2 %
Flash Point	: Non Flammable
Colour	: Please consult KCC representative for standard colours
Finish	: Low Sheen

Application Information

Substrate	: Concrete, Masonry, Soft Board, Roof Tiles
Recommended No. of Coats	: 2
Recommended Wet Film Thickness	: 100 µm / Coat
Recommended Dry Film Thickness	: 40 µm / Coat
Theoretical Spreading Rate @ 40µm	: 10 m ² / L / Coat
<small>(Does not include substrate condition and loss factors)</small>	
Drying Agent	: Evaporation, Coalescence
Drying Time	: Touch Dry 30 min Recoat 45 min

Application Methods

Applied By	: Brush / Roller / Spray
Thinner	: Clean Water
Clean Up	: Clean Water

Packaging & Storage

Packaging	: 5L
Shelf Life	: 12 months - Unopened
Storage	: Cool, dry and well ventilated area away from heat and direct sun light. Lid must be kept tightly closed.

Disclaimer : The above information is given to the best of our knowledge based on laboratory testing and practical experiences. The information in this data sheet may be subject to changes from time to time and without notice due to production refinements arising from continuing research and evaluation programmes, which may occasionally result in marginal changes in the coating properties.

Surface Preparation

New Masonry Substrate

Allow all new surfaces to dry out thoroughly, preferably for at least 28 days drying time or check moisture content for less than 16%. Surface imperfections, misalignments and protrusions shall be made good and patched up. All surface contaminants such as laitance, dust and loose cement shall be removed using scraper, sandpapers and clean stilt brushes.

Previously Painted Surfaces

All loose or defective paintwork or powdery residues shall be thoroughly removed by high pressure water jet cleaning. Treat any areas affected by mould, lichens, algae and moss with "KCC Fungicidal Solution". Make good minor defects with an appropriate suitable exterior putty sealant.

Typical Recommended Painting System

Substrate: Concrete, Masonry, Soft Board, Roof Tiles

<u>System</u>	<u>Product</u>	<u>No. of Coats</u>
Sealer	Koresil 450	1
Finish	RoofCare	2

Substrate: Previously Painted Concrete, Masonry, Soft Board, Roof Tiles

<u>System</u>	<u>Product</u>	<u>No. of Coats</u>
Sealer	Koresil 401	1
Finish	RoofCare	2

Application & Cleaning Instructions

Paint is ready for use after thorough stirring. Thinning is not normally necessary, however, if required for better workability, do not exceed 5% of dilution ratio. Clean up equipment with water immediately after use.

Health & Safety

Ensure good ventilation during application and drying. Avoid contact with skin and eyes. In case of contact with eyes, rinse immediately with plenty of water and seek medical advice. After contact with skin, wash immediately with plenty of soap and water. During spray application, do not breathe in mist and wear suitable respiratory protective equipment. Keep out of reach of children.

Disclaimer : The above information is given to the best of our knowledge based on laboratory testing and practical experiences. The information in this data sheet may be subject to changes from time to time and without notice due to production refinements arising from continuing research and evaluation programmes, which may occasionally result in marginal changes in the coating properties.