



KORESKIM BASE COAT 110

Mold Resistant Interior Base



Koreskim Base Coat 110 Mold-Resistant Interior Base is a high-performance plastering compound designed for interior walls and ceilings. Formulated with natural powders, eco-conscious composite additives, and water-repellent components, it offers excellent breathability and strong adhesion to substrates.



**Effectively Conceals
Surface Imperfections**



**Excellent
Workability**



**Anti-Mildew
& Water Resistant**



**Odorless & Health-
conscious Formulation**

WHERE TO USE

Perfect for creating smooth, even surfaces on interior walls and ceilings, even in damp conditions or where maximum adhesion is critical

PRODUCT DATA

Appearance	White / Grey Powder
Packing Size	40.0 kg per bag
Theoretical Coverage	1.00 - 1.50 kg / m ² / Coat (Note: Actual coverage varies based on substrate type, surface porosity, and texture)
Pot Life	2 hours (Room Temperature)
Colour Range	White / Grey
Construction Tools	Blender, mixing bucket, mud shovel, trowel, and spatula
Shelf Life	12 months - Unopened

KORESKIM BASE COAT 110

Mold Resistant Interior Base

APPLICATION INSTRUCTIONS



Surface Preparation

- Ensure the substrate is completely dry, structurally sound, and free from oil stains, dust, loose particles, or any peeling materials.
- Clean any powdery or flaking areas thoroughly before application.



Mixing

- Add water as recommended.
- Mix for 3–5 minutes with an electric mixer.
- Allow the mixture to rest for 3–5 minutes, then remix to get a smooth, even consistency.



Application

- Apply using a spatula or a suitable tool.
- Each coat should be applied at a thickness of **2 to 4 mm**.
- For areas requiring more than 4 mm of leveling, apply in multiple thin layers rather than a single thick coat.



Recoating

- Let each coat dry completely before the next.
- Drying time depends on temperature, humidity, and substrate condition.

HANDLING PRECAUTIONS

Use only clean water for mixing (no additives), apply in ambient temperatures between **5°C – 35°C**. Avoid application during rainy weather or on damp substrates. Use within **2 hours at 25°C** without re-adding water, moisten walls and apply two coats with a **2-hour gap** in hot conditions. Once the sealed bag is opened, use the product immediately to prevent moisture contamination.

TRANSPORTATION & STORAGE

Protect the product from rain, moisture, and impact during transport. Store in a cool, dry, well-ventilated place, away from water.

Shelf life under proper storage and transport conditions:

- 12 months for paper bag packaging
- 6 months for woven bag packaging

SIRIM TEST REPORT



TECHNOLOGY



BUATAN MALAYSIA



KCC Paints Sdn. Bhd. 199401038283 (323967-T)

No.1, Jalan Anggerik Mokara 31/55, Seksyen 31, Kota Kemuning, 40460 Shah Alam, Selangor Darul Ehsan.
Tel : 03-5122 2900 Fax : 03-5122 1900 www.kccpaint.com.my